

E-MOBILITY

KeContact P30 a-series

Easy and safe charging at home



KEBA Article No.	KEBA Product Description	1-phase	3-phase	Available starting
119 921	a-series EN Type2 3p Socket 22kW		●	06.April 2021
119 922	a-series EN Type2 3p Socket+Shutter 22kW		●	06.April 2021
119 923	a-series EN Type2 3p 6m Cable 22kW		●	06.April 2021
119 924	a-series EN Type2 3p 6m Cable 11kW		●	06.April 2021
119 925	a-series EN Type2 3p Socket 22kW-RFID		●	06.April 2021
119 926	a-series EN Type2 3p Socket+Shutter 22kW-RFID		●	06.April 2021
119 927	a-series EN Type2 3p 6m Cable 22kW-RFID		●	06.April 2021
119 928	a-series EN Type2 3p 6m Cable 11kW-RFID		●	06.April 2021
120 280	a-series EN Type2 1p Socket 7,4kW	●		03.May 2021
120 281	a-series EN Type2 1p Socket+Shutter 7,4kW	●		03.May 2021
120 283	a-series EN Type2 1p 6m Cable 7,4 kW	●		03.May 2021
120 284	a-series EN Type2 1p Socket 7,4kW-RFID	●		03.May 2021
120 285	a-series EN Type2 1p Socket+Shutter 7,4kW-RFID	●		03.May 2021
120 286	a-series EN Type2 1p 6m Cable 7,4 kW-RFID	●		03.May 2021

Specifications

Rated current 7,4 kW bzw. 22 kW	10A, 13A, 16A, 20A, 25A, 32A
Rated current 11 kW	10A, 13A, 16A

Interfaces

<ul style="list-style-type: none"> • Enable input for external authorisation
<ul style="list-style-type: none"> • Potential-free switch contact output
<ul style="list-style-type: none"> • Ethernet connection RJ45 (for debug)
<ul style="list-style-type: none"> • USB 2.0 connection type A

Dimensions, Colours

Dimensions (W x H x D) Socket or socket+shutter variant:	240 x 495 x 166 mm
Dimensions (W x H x D) Cable variant:	240 x 643 x 140 mm
Colour	RAL 9010 (pure white) / RAL 7016 (anthracite grey) with printed KEBA logo

Certifications

CE - Declaration of Conformity	yes
--------------------------------	-----