

KeContact P30 – Equipment series

KeContact P30 is available in four different equipment series. The series are built upon each other, which means that, when purchasing a higher value system, you also receive the features listed for the lower value system. The **e-series** is the entry-level variant of the KeContact P30 for easy, cost-optimized charging. KeContact P30 **b-series** offers a large degree of custom branding possibilities, user authorization possibilities and 22kW fast charging. The KeContact P30 **c-series** is a communication interface for intelligently controlled charging and smart home applications. Creating comprehensive e-mobility solutions such as local load management requires the **x-series**. This means you will always find the appropriate charging station for your needs!

Four equipment series for your needs:



| |
|-------------------------------------------------------------------------------------|
| WLAN communication for the wireless integration of wallboxes in an existing network |
| GSM (3G) for wireless communication to OCPP backend |
| Communication to external energy meter via modbus TCP |

| | |
|------------------------------------------------------|------------------------------------------------------|
| Local load management as a slave | Local load management as a master |
| OCPP communication as a slave | OCPP communication as a master |
| Slave for Master/Slave communication | Master for Master/Slave communication |
| UDP interface (smart home automation) | UDP interface (smart home automation) |
| Ethernet interface for permanent installation (LSA+) | Ethernet interface for permanent installation (LSA+) |
| Metering (MID certified*) for billing purposes | Metering (MID certified*) for billing purposes |
| Authorization (RFID, Key) | Authorization (RFID) |
| Enable input / Switch output | Enable input / Switch output |
| Overcurrent detection | Overcurrent detection |
| Customizing / branding | Customizing / branding |
| DC leakage detection | DC leakage detection |
| Ethernet interface (RJ45) | Ethernet interface (RJ45) |
| USB interface | USB interface |
| e-series | b-series |
| Single phase up to 20A (4.6kW) | Three phase up to 32A (22kW) |
| VDE certified* | VDE certified* |

| | |
|--------------------------------|------------------------------|
| Authorization (RFID, Key) | Authorization (RFID) |
| Enable input / Switch output | Enable input / Switch output |
| Overcurrent detection | Overcurrent detection |
| Customizing / branding | Customizing / branding |
| DC leakage detection | DC leakage detection |
| Ethernet interface (RJ45) | Ethernet interface (RJ45) |
| USB interface | USB interface |
| e-series | b-series |
| Single phase up to 20A (4.6kW) | Three phase up to 32A (22kW) |
| VDE certified* | VDE certified* |

* available in 2018



THE MOBILITY HOUSE
mobilityhouse.com

Sales partner



Automation by innovation.